

Borough Council of King's Lynn and West Norfolk Level 2 Strategic Flood Risk Assessment Detailed Site Summary Tables

Site details		
Site Code	GT56	
Address	Wheatley Bank, Walsoken (South of Worzals paralell to A47)	
Area	1.6ha	
Current land use	Authorised Gypsy & Traveller Site	
Proposed land use	Gypsy & Traveller Site	
Flood Risk Vulnerability	Highly Vulnerable	
Sources of flood risk		
Location of the site within the catchment	The site is located within the King's Lynn IDB area, and is drained by a complex network of drainage channels, which discharge into the River Nene to the East and River Great Ouse to the West. These two rivers are tidal through the IDB area and flow into the sea at the Wash, approximately 15km north of the site.	
Topography	The site and most of the surrounding area is very flat and low lying. The site slopes downward slightly from east to west with a maximum elevation of 2.7m AOD and minimum elevation of 2.0m AOD. The town of Walsoken to the south-west is elevated above the surrounding area.	
Existing drainage features	There are several small drainage channels within the vicinity of the site which form part of the IDB drainage network, including channels along the north and west boundaries. There are no major channels within the vicinity of the site.	
Fluvial and tidal	The proportion of site at risk FMFP: FZ3 - 0% FZ2 - 68% FZ1 - 0% Fluvial model outputs: 3.3% AEP fluvial event - 0% 1% AEP fluvial event - 0% 0.1% AEP fluvial event - 0% Breach Fluvial model outputs: 1% AEP fluvial event - 0% Defended Tidal Model Outputs 3.3% AEP tidal event - 0% 1% AEP tidal event - 0% 0.5% AEP tidal event - 0% 0.1% AEP tidal event - 0%	

Undefended Tidal Model Outputs

3.3% AEP tidal event – 0% 1% AEP tidal event – 0% 0.5% AEP tidal event – 0% 0.1% AEP tidal event – 68%

Available data:

Fluvial outputs are taken from the Environment Agency's Fenlands Flood Risk Mapping Model (2015). Undefended runs have not been undertaken since the Fenlands in its current form exists only due to the long history of land drainage and continuous management by the IDB. Rather, there is composite breach mapping available which represents the risk due to failure of embankments and key management assets during the 1% AEP scenario. Tidal outputs are taken from the Environment Agency's The Wash Model (2018).

Flood characteristics:

The site is within the EA's FMfP Flood Zone 2.

The site is shown to be at low risk in all fluvial modelled events, including in the modelled breach events.

The site is protected by tidal defences to a standard greater than the 0.1% AEP event, including an allowance for climate change.

In undefended scenarios, the site is at low risk up to the 0.5% AEP event. In the 0.1% AEP tidal undefended event, depths across the site reach approximately 0.6m and hazard on site reaches 'Danger for most', although is low across most of the flooded area. This means that in the event that tidal defences were to fail during an extreme event, occupants of the site may be at significant risk, and the nature of defence failure means that the speed of onset of flooding could be rapid. It is noted that there are currently questions as to the funding of defences around the King's Lynn area for the long term, and maintenance of these defences could affect the risk to the site throughout its lifetime.

Given this, and the widespread nature of flooding in the area, a flood warning and evacuation plan which considers the Highly Vulnerable nature of the site and its location on a potential dry island will be essential if the site is to be brought forward. This plan should consider the speed of onset of flooding, and it may not be appropriate for residents to occupy the site during events where the defences are operational as a precaution in case of breach.

Proportion of site at risk (RoFfSW):

3.3% AEP - 0%

Max depth - N/A

Max velocity – N/A

1% AEP - <1%

Max depth - 0.3-0.6m

Max velocity – <0.25m/s

0.1% AEP – 4.1%

Max depth - 0.6-0.9m

Max velocity - < 0.25 m/s

Description of surface water flow paths:

The site is in a rural area which is generally well drained by the network of IDB drainage channels, and there is very little risk of surface water flooding to the site identified even in 3.3% AEP event. In the 1% AEP event,

Surface Water

	surface water flows paths are shown, though these are associated with the drainage channels and are unlikely to pose a risk to occupants of the site. In the 0.1% AEP event, alongside the surface water flows associated with the drainage channels, an area of minor ponding forms in the east of the site. Depths, hazard and velocities in this area are all low and unlikely to pose a risk to users of the site. The majority of the site remains unaffected, and the ponding will not affect access and egress. Development should be steered away from these areas of risk.	
Reservoir	There are no reservoirs which could pose a risk to the site in event of an uncontrolled release.	
Groundwater	The site is within an area where there is considered to be a very low risk of groundwater emergence.	
Sewers	Anglian Water's Sewer Flooding register was not available for this assessment.	
Flood history	The site is not within the Environment Agency's recorded flood outlines dataset. Historic Flood Records from the LLFA were not available to support this assessment.	
Flood risk management infrastructure		
Defences	The site is protected by embankments and engineered high ground along the coastline to the north and River Great Ouse to the east. The embankments are owned and operated by the Environment Agency and are recorded to give protection up to the 1% AEP event, although modelling suggests they will protect the site up to the 0.1% AEP event including climate change.	
Residual risk	The site is shown to be at significant risk (hazard rating: danger to most) in the undefended 0.1% AEP tidal event. Therefore, the site would be at considerable risk in the event of a breach or failure of defences during an extreme event.	
Emergency planning		
Flood warning	The site lies within the Environment Agency's 'Tidal Great Ouse from Denver to south of King's Lynn in Norfolk' Flood Alert Area. The site lies within the Environment Agency's 'Tidal breach east of Wisbech along the A47 at West Walton, Emneth Hungate, and Terrington St John' Flood Warning Area.	
Access and egress	Access and egress to the site is from Wheatley Bank. Access and egress to the site is unlikely to be affected in any fluvial or surface water event. During undefended tidal events, access and egress to the site is unlikely to be affected up to the 0.5% AEP tidal event. During the 0.1% AEP undefended tidal event, the site is at significant risk with a hazard rating of "Danger to Most" to "Danger to All", and access/egress may be impeded. Given the Highly Vulnerable nature of the development, a Flood Warning and Evacuation Plan will be essential to bringing forward the site. This should consider the 'Highly Vulnerable' nature of the site and the potential for the rapid onset of flooding if defences were to breach.	

Dry Islands

Part of the site is located within a potential dry island during the 0.1% AEP undefended tidal flood events.

Climate change

Management Catchment: North West Norfolk

Fluvial Flooding (Fenlands Flood Risk Mapping):

The site is not shown to be at risk in either the 1% AEP baseline or breach fluvial event including climate change from the Environment Agency's Fenland Flood Risk Mapping model.

Tidal Defended:

The site is not shown to be at risk in the 0.1% AEP +CC (2115 epoch) tidal defended event.

Tidal Undefended/Breaches:

Implications for the site

In the undefended/breach scenarios, the site is shown to be highly sensitive to climate change. The site is not shown to be at risk during the 0.5% AEP undefended tidal event, however the entire site is at risk during the 0.5% AEP tidal undefended event in the 2115 epoch. Depths on site during the 0.5% AEP Tidal event are up to 2.2m with climate change, with hazard classification of 'Danger for All'. In the 0.1% AEP event, depths reach up to 2.5m. Flood warning and evacuation plans should consider the increase in risk to the site in future due to climate change and present a plan that ensures residents to the site can be safely evacuated in the 0.1% AEP event including an allowance for climate change.

Surface Water:

Climate change allowances have not been applied to the Environment Agency's Risk of Flooding from Surface Water Dataset for this assessment. However a comparison of the extent of the 1% AEP surface water event to the 0.1% AEP surface water event suggests that the site is not sensitive to increases in surface water risk as a result of climate change. Areas at risk are likely to remain confined to the drainage channels and topographic low points, and development on site should be steered away from these areas.

NPPF and planning implications

The Local Authority will need to confirm that the Sequential Test has been carried out in line with national guidelines. The Sequential Test will need to be passed before the Exception Test is applied.

The NPPF classifies Gypsy and Traveller Sites as "Highly Vulnerable". As the entire site is within Flood Zone 2, the Exception Test will be required.

Exception Test requirements

It would be sequentially preferable for Highly Vulnerable development to be placed outside Flood Zones; however, the Borough Council of King's Lynn and West Norfolk has engaged with the Environment Agency in their approach, and demonstrated through a documented sequential screening process (see Main Report) that there are not sufficient sites outside Flood Zones to meet the required need. Therefore, this site has been taken forward for consultation.

As the site is within Flood Zone 2, and classified as 'Highly Vulnerable', the Exception Test is required for this site.

Flood Risk Assessment:

Appendix C of the Level 2 SFRA and Sections 8 and 9 of the Level 1 SFRA have more guidance on this section and any relevant policies and information applicable to development within King's Lynn and West Norfolk borough. The Level 2 SFRA Addendum contains a summary of changes in legislation since the Level 1 and Level 2 SFRAs were completed.

- Consultation with the Borough Council of King's Lynn and West Norfolk, Anglian Water, King's Lynn IDB, and the Environment Agency should be undertaken at an early stage.
- Developers should consult with Anglian Water to ensure that the development aims to help achieve the targets of the Drainage and Wastewater Management Plan.
- Any FRA should be carried out in line with the National Planning Policy Framework; Flood Risk and Coastal Change Planning Practice Guidance; Borough Council of King's Lynn and West Norfolk's Local Plan Policies and Sustainable Drainage Design and Evaluation Guide for developers.
- Flood Risk Assessments should be informed by detailed modelling including depth, velocity and hazard outputs, including an allowance for climate change.

Guidance for site design and making development safe:

- The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF's policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG).
- This development is proposed in an area that is at risk during the 0.1% AEP undefended tidal event; careful consideration will need to be given to flood resistance and resilience measures and an appropriate Flood Warning and Evacuation Plan will be essential.
- The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, so runoff magnitudes from the development are not increased by development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure runoff rates are as close as possible to greenfield rates.
- Planning permission is required to surface more than 5 square metres of unpaved ground using a material that cannot absorb water.
- Arrangements for safe access and egress will need to be demonstrated for the 0.1% AEP tidal event and surface water events with an appropriate allowance for climate change, using the depth, velocity, and hazard outputs. As access and egress will not be possible during tidal breach events, a Flood Warning and Evacuation Plan will be required.
- Consultation with RMAs early on should be implemented to ensure an appropriate flood evacuation plan is put in place for the site. This should consider the Highly Vulnerable nature of residents, widespread extents of flooding, and potential for rapid inundation of the site in event of breach.
- Flood resilience and resistance measures should be implemented where appropriate during the construction phase, e.g. raising of floor

Requirements and guidance for site-specific Flood Risk Assessment levels. These measures should be assessed to make sure that flooding is not increased elsewhere. If floor levels cannot be raised to meet the minimum requirements, developers will need to:

- · raise them as much as possible
- include extra flood resistance and resilience measures.
- Other examples of flood resistance and resilience measures include:
 - using flood resistant materials that have low permeability to at least 600mm above the estimated flood level
 - making sure any doors, windows or other openings are flood resistant to at least 600mm above the estimated flood level
 - by raising all sensitive electrical equipment, wiring and sockets to at least 600mm above the estimated flood level.

Key messages

In the defended scenario, the site is generally at low risk from all sources. However, the site is 'Highly Vulnerable', within Flood Zone 2, and shown to be at significant risk of tidal flooding in the event of a breach or failure during an extreme event. Normally, Highly Vulnerable uses would not be preferable within Flood Zone 2. However, considering the wide extent of Flood Zones within the Borough, and the Borough's evidence demonstrating a clear need and lack of lower risk suitable sites, it may be appropriate to develop the site provided:

- A site-specific Flood Risk Assessment, supported by detailed modelling demonstrates users of the site are not at risk of flooding from fluvial, tidal and surface water sources during the 0.1% AEP event including an allowance for Climate Change.
- An appropriate Flood Warning and Evacuation Plan is prepared for the site, which considers the Highly Vulnerable nature of the site and its users, the potential for rapid onset of flooding, and the potential widespread nature of flooding affecting access routes. The plan will need to demonstrate that users of the site can be warned and evacuated safely during the 0.1% AEP tidal event, including an allowance for climate change. Given the risk of rapid inundation during a breach, it may be determined that the site be evacuated as a precaution whenever the defences are considered actively holding back flooding.

Mapping Information

11 3		
Flood Zones	Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Map for Planning mapping.	
Climate change	Climate change runs from the Environment Agency's Fenlands Flood Risk Mapping and The Wash Models have been used in this assessment.	
Fluvial and tidal extents, depth, velocity and hazard mapping	Fluvial outputs are taken from the Environment Agency's Fenlands Flood Risk Mapping Model (2015). Undefended runs have not been undertaken since the Fenlands in its current form exists only due to the long history of land drainage and continuous management by the IDB. Rather, there is composite breach mapping available which represents the risk due to failure of embankments and key management assets during the 1% AEP scenario. Tidal outputs are taken from the Environment Agency's The Wash Model (2018).	
Surface Water	The Environment Agency's Risk of Flooding from Surface Water dataset has been used for this assessment.	

Surface water depth, velocity and hazard mapping

The Environment Agency's Risk of Flooding from Surface Water dataset has been used for this assessment.